## **PCT**

# WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:

C11D 7/54, 7/32

(11) International Publication Number: WO 97/45523

(43) International Publication Date: 4 December 1997 (04.12.97)

(21) International Application Number: PCT/NL97/00294

(22) International Filing Date: 26 May 1997 (26.05.97)

(30) Priority Data:

1003225 29 May 1996 (29.05.96) NL

(71) Applicants (for all designated States except US): HEINEKEN TECHNICAL SERVICES B.V. [NIJNL]; 2e Wetering-plantsoen 21, NL-1017 ZD Amsterdam (NL). LHS MICRO-FILTRATIONS B.V. [NL/NL]; Opaalstraat 22, NL-7554 TS Hengelo (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): MOL, Martinus, Nicolaas, Maria [NL/NL]; Turfmarkt 3, NL-2312 CD Leiden (NL). VAN HOOF, Stephan, Cornelus, Johannes, Maria [NL/NL]; Troelstraweg 167, NL-6702 AK Wageningen (NL).

(74) Agent: SMULDERS, Th., A., H., J.; Vereenigde Octrooibureaux, Nieuwe Parklaan 97, NL-2587 BN The Hague (NL).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

#### **Published**

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

In English translation (filed in Dutch).

(54) Title: METHOD FOR CLEANING ITEMS IN PARTICULAR FILTERS, USED DURING FOODSTUFF PRODUCTION

(57) Abstract

The invention relates to a method for cleaning apparatus used during the production of foodstuffs, in particular the filtration thereof, wherein this apparatus is contacted after use with a cleaning system based on the combination of a cyclic nitroxyl compound and a hypohalite.

BEST AVAILABLE COPY

### FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

	AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
			FI	Finland	LT	Lithuania	SK	Slovakia
	AM	Armenia	FR	•	LU	Luxembourg	SN	Senegal
	AT	Austria		Prance	LV	Latvia	SZ	Swaziland
	AU	Australia	GA	Gabon				
	ΑZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
	BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
ĺ	BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
l	BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
	BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
	BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
	BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
	BR	Brazil	11.	Israel	MR	Mauritania	UG	Uganda
	BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
ŀ	CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
	CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
	CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
١	CH	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
١	Cl	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
Į	CM	Cameroon		Republic of Korea	PL	Poland		
l	CN	China	KR	Republic of Korea	PT	Portugal		
ĺ	CU	Cuba	KZ	Kazakstan	RO	Romania		
1	CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
١	DE	Germany	Ll	Liechtenstein	SD	Sudan		
ı	DK	Denmark	LK	Sri Lanka	SE	Sweden		
l	RE	Estonia	LR	Liberia	SG	Singapore		
l								

BEST AVAILABLE COPY

WO 97/45523

# METHOD FOR CLEANING ITEMS IN PARTICULAR FILTERS, USED DURING FOODSTUFF PRODUCTION

The invention relates to the cleaning of apparatus used during the production, processing or treatment of foodstuffs, more in particular the filtering thereof. An important example thereof is the cleaning of apparatus for brewing beer and more in particular the cleaning of filters, such as membrane filters for filtering residual beer and settled beer. Within the context of this invention the term "production" is used to indicate all treatments carried out on foodstuffs, such as production, treatment, processing and the like.

5

10

15

20

25

During the production of foodstuffs, such as milk (products), fruit juices, beer, soft drinks (such as lemonades), cider, wine, sherry, port, distilled drinks and the like, the problem often occurs that apparatus must be cleaned after a certain period, because components from the material to be treated are adsorbed or absorbed or precipitate on surfaces of the apparatus, which is undesirable. This may in fact give rise to a disturbance of, on the one hand, the operation of the apparatus and, on the other hand, the quality of the final product.

The apparatus involved is the apparatus used during the treatment of foodstuffs, more in particular liquids, as indicated above. More in particular, filters are involved, such as membrane filters used for filtering the above products or semimanufactures therefor.

Examples of such treatments are the production and/or processing of milk and milk products, fruit juices, beer, soft drinks, cider, wine, sherry, port, distilled drinks and the like.

In the case of brewing beer the invention relates to, inter alia, the apparatus used during the preparation of malt, the conversion of malt and/or unmalted grain into wort and the further processing of the wort, with or without

10

15

20

25

30

35

addition of extra components, such as hops, by fermentation to beer, as well as all auxiliary apparatus used therewith and coming in contact with main or secondary streams from these processes.

An example of the disturbance of the operation of the apparatus is found with the different filters used, e.g. the filters for filtering soft drinks, milk (products), wine, sherry, port, distilled drinks, fruit juices, lemonade, beer, such as settled beer, residual beer, but also the wort/spent grain separation, hot trub separation and cold trub separation.

The capacity of filters used in such processes, the flux, decreases in the course of time, which is of course undesirable. This particularly plays a role when use is made of membrane filters. This capacity decrease can be partly inhibited by rinsing back the filter. After some time, however, this is not sufficient, and it is therefore necessary to clean the filter.

A further examination has revealed that the apparatus, and more in particular the filters, become contaminated by a combination of all kinds of compounds, of which polysaccharides, oligosaccharides, proteins,  $\beta$ -glucanes, fats and polyphenols are important components. during the production

Conventional cleaning techniques, e.g. based on catalyzed or uncatalyzed oxidation, e.g. with a peroxide/metal (manganese) complex hypochlorite or hypobromite, are not satisfactory, which appears from the fact that the flux cannot be restored to the original value or close thereto. Nor does the use of detergents or enzymes, such as proteases, carbohydrases, amylases, pullulanases, proteases and lipases, lead to the desired results.

There is therefore a need for an efficient cleaning system for cleaning apparatus for the production, as defined above, of liquid foodstuffs, which system is capable of effecting a proper cleaning, which must preferably be done

15

20

30

35

within a short time (15-120 min) and during which substantially all contaminations are removed.

The invention is based on the surprising insight that it is possible to adequately clean apparatus used during the production of foodstuffs by using a cleaning system on the basis of a combination of a cyclic nitroxyl compound and a hypohalite. This involves removal of contaminations formed during the production of foodstuffs, e.g. precipitated on surfaces of the apparatus or in pores of filters.

The invention therefore relates to a method for cleaning apparatus used during the production of foodstuffs, in which this apparatus is contacted after use with a cleaning system based on the combination of a cyclic nitroxyl compound and a hypohalite in aqueous solution.

Preferably, the cyclic nitroxyl compound is a substituted piperidine, such as 2,2,6,6-tetramethylpiperidine-N-oxyl (TEMPO). This is a commercially available compound (CAS Reg. No. 2564-83-2).

In combination with a hypohalite, preferably a hypobromite, it is possible to obtain a rapid removal of contaminations by using catalytic amounts of TEMPO. The hypobromite, which is preferred, is preferably formed in situ from hypochlorite and alkali metal bromide (most preferably NaBr), so that the reaction system of Fig. 1 is obtained. It is to be noted that preference is given to the use of 25 bromite, since it gives a considerably shorter cleaning time than the chlorite. It is also possible to generate the bromite from other components or to add it as such to the system.

The method according to the invention is most preferably carried out by contacting an aqueous solution of the nitroxyl compound, such as the different nitroxide radicals, e.g. 2,2,6,6-tetra-methylpiperidine-N-oxyl (TEMPO), 4-oxo-2,2,6,6-tetra-methylpiperidine-N-oxyl (OTEMPO), 4hydroxy-2,2,6,6-tetra-methylpiperidine-N-oxyl (TEMPOL) and other derivatives having the same 2,2,6,6-tetra-

10

15

20

25

30

35

methylpiperidine-N-oxyl (TEMPO) skeleton, as well as derivatives on the basis of 4,4-dimethyloxazolidine-N-oxyl (DOXYL) and 2,2,5,5-tetra-methylpyrrolidine-N-oxyl (PROXYL) and the hypohalite in water with the contaminated apparatus.

The concentration of the cyclic nitroxyl compound preferably ranges between 1 and 250 mg/l, more in particular between 2 and 25 mg/l. Such concentrations of nitroxyl compound can be properly combined with hypohalite (OBr or OCl) concentrations of at least 0.5 g/l, preferably 0.75 to 10 g/l. In case a system on the basis of hypochlorite, alkali metal bromide and the nitroxyl compound is used, the amount of bromide is significantly lower than the amount of hypochlorite. Since the bromite is regenerated, bromide contents (calculated as Br) of not more than 1 g/l are sufficient at the above concentrations of the nitroxyl compound.

In a characteristic method a catalytic amount of TEMPO is used. Only minute amounts of the cyclic nitroxyl compound are necessary, since it functions as a catalyst for forming the active oxidant, the hypohalite, from hypohalide.

It is to be noted in this respect that the present system of cyclic nitroxyl compound and hypohalide is known per se, e.g. from WO-A 95/07303. This publication describes the oxidation of carbohydrates with primary hydroxyl groups. In no manner, however, does it appear therefrom that this system is useful for cleaning apparatus used for the production of foodstuffs, in which the nature of the

contaminations is as different as indicated above. This is the more surprising as the conventional cleaning methods on the basis of hypohalite, e.g. with filters when brewing beer, do not give the desired effect.

The invention is applicable to all apparatus used during the processing of foodstuffs, and which contacts the main stream and/or the secondary streams of the production. More in particular, the invention is applicable to the cleaning of filters used for filtering milk, milk products,

10

15

20

25

30

35

soft drinks, cider, wine, sherry, port, fruit juices, distilled drinks, beer, settled beer, residual beer, but also the wort/spent grain separation, hot trub separation and cold trub separation.

The contact between cleaning liquid and apparatus may be effected both statically and dynamically, that is to say: the liquid either is stationary or flows through the apparatus. Suitable contact times range between 5 minutes and 2 hours, which times of course also depend on the degree of contamination, the concentration of the components (more in particular the nitroxyl compound) and the temperature.

The pH of the cleaning liquid is preferably kept within the alkaline range. In practice, this is a value ranging between 7 and 12. When using only hypochlorite in combination with the nitroxyl compound, even weakly acid pH values are possible (pH>6). Since the cleaning is often accompanied with the formation of organic acids, the cleaning can be controlled by means of the amount of caustic required to maintain the adjusted pH. As soon as the caustic consumption strongly decreases, also after dosing HOCl/HOBr, it can be noticed that the cleaning is terminated. This system has the great advantage that a low concentration of oxidant is sufficient, so that damage to apparatus and parts can be decreased or even completely avoided.

After cleaning the apparatus is rinsed and can be used again. It is to be noted that the system according to the invention can be suitably used for each cleaning. It is also possible, however, to alternately clean the apparatus with, on the one hand, a conventional system, e.g. based on detergents, optionally in combination with peroxides and/or enzymes, and, on the other hand, the system according to the invention. It is also possible to use the system according to the invention as a kind of postcleaning, subsequent to a conventional system.

The invention will now be explained by means of some, non-limitative, examples.

15

#### EXAMPLE 1

By means of a module for filtering settled beer, which was provided with a non-used membrane filter, settled beer was filtered for some time at a pressure of 0.3 bar. The flux of the beer was determined at a number of times (A).

Then the filter was cleaned for 2 hours with a solution containing 4.5 g/l HOCl, 35 mg/l NaBr and 15 mg/l TEMPO. After the cleaning the test was repeated (B). This cycle was then carried out one more time (C). In the following table some results are listed.

Table

Flux (1/hour/bar/m²)

Time (min)	Α	В	C
20	1100	1100	1400
30	850	1050	1100

10

25

#### Claims

- 1. A method for cleaning apparatus, more in particular a filter, used during the production of foodstuffs, wherein said apparatus is contacted after use with a cleaning system based on the combination of a cyclic nitroxyl compound and a hypohalite.
- 2. A method according to claim 1, wherein apparatus, more in particular a filter used for producing (filtering) milk (products), fruit juices, beer, soft drinks, such as lemonades, cider, wine, sherry, port, distilled drinks and the like, more in particular beer, is cleaned.
- 3. A method according to claim 1 or 2, wherein a membrane filter is cleaned.
- 4. A method according to claims 1-3, wherein the cyclic nitroxyl compound is used in a catalytic amount.
- 15 5. A method according to claims 1-4, wherein the cyclic nitroxyl compound used is 2,2,6,6-tetra-methylpiperidine-N-oxyl (TEMPO), 4-oxo-2,2,6,6-tetra-methylpiperidine-N-oxyl (OTEMPO), 4-hydroxy-2,2,6,6-tetra-methylpiperidine-N-oxyl (TEMPOL) and other derivatives having the same 2,2,6,6-tetra-methylpiperidine-N-oxyl (TEMPO) skeleton, as well as derivatives on the basis of 4,4-dimethyloxazolidine-N-oxyl (DOXYL) and 2,2,5,5-tetra-methylpyrrolidine-N-oxyl (PROXYL),
  - (TEMPO).

    6. A method according to claims 1-5, wherein the

more in particular 2,2,6,6-tetra-methylpiperidine-N-oxyl

- 7. A method according to claims 1-6, wherein the hypohalite used is a combination of hypochlorite and an alkali bromide.
- 30 8. A method according to claims 1-7, wherein the cleaning system is used as an aqueous solution.

hypohalite used is a hypobromite.

WO 97/45523 PCT/NL97/00294

8

- 9. A method according to claims 1-8, wherein said cleaning is preceded by a cleaning with another cleaning system.
- 10. A method for producing one or more foodstuffs, more in particular beer, in suitable apparatus, wherein said apparatus is regularly cleaned using the method according to any or more of claims 1-9.
- 11. The use of a cleaning system based on the combination of a cyclic nitroxyl compound, preferably in combination with a hypohalite, for cleaning apparatus used for the production, more in particular the filtering, of foodstuffs.

L CLASSIFI	C11D7/54 C11D7/32		
losording to (	International Patent Classification (IPC) or to both national class	ification and IPC	
3. FIELDS S			
Minimum doo IPC 6	sumentation searched (classification system followed by classifi C110	oation symbols)	
Documentatio	on searched other than minimum documentation to the extent th	at such documents are included in the fields sea	rched
Electronio da	ata base consulted during the international search (name of data	a base and, where practical, search terms used)	
C. DOCUME	ENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the	a relevant passages	Relevant to claim No.
A	DATABASE WPI Section Ch, Week 9323 Derwent Publications Ltd., Lor Class A97, AN 93-186697 XP002024217 & RO 104 553 A (DERO INTR DETE February 1992 see abstract		1,8
A	DE 36 35 357 A (WELLHOENER VE 1988 see the whole document	IT) 21 April	1
A	EP 0 392 395 A (GESSNER & CO 0 0ctober 1990 see page 9, line 20 - line 25		1-3,9
Fur	rther documents are listed in the continuation of box C.	X Patent family members are listed	in annex.
"A" docum consi "E" earlier filing "L" docum white citati "O" docum other	nent defining the general state of the art which is not idered to be of particular relevance or document but published on or after the international date on the case of the state of the s	"I" later document published after the interpretation or priority date and not in conflict with oited to understand the principle or the invention.  "X" document of particular relevance; the cannot be considered novel or cannot involve an inventive step when the description of the involve and inventive and the cannot be considered to involve and document is combined with one or a menta, such combination being obvious the art.  "&" document member of the same pater.	in the application but heavy underlying the claimed invention of be considered to comment is taken alone claimed invention inventive step when the more other such docurous to a person skilled
	e actual completion of the international search  9 October 1997	Date of mailing of the international set	earch report
	d mailing address of the ISA  European Patent Office, P.B. 5818 Patentiaan 2  NL - 2280 HV Rijswrijk  Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Authorized officer  Grittern, A	

## INTERNATIONAL SEARCH KEPUKI

...formation on patent family members

Inter Inst Application No
PCT/NL 97/00294

Patent document cited in search report	Publication date	Patent family member(s)	Publication date	
DE 3635357 A	21-04-88	NONE	<del></del>	
EP 0392395 A	17-10-90	DE 3911697 A JP 3117475 A	25-10-90 20-05-91	